

IRANOL EP is produced using high-quality paraffinic base oil, derived from the distillation of crude oil, and appropriate extreme pressure additives.

► Performance Levels

- API GL-4
- INSO 2873

► Applications

- In all non-automatic gearboxes of light and heavy vehicles and other vehicles, also in all power transmission systems that meet the above performance levels.

*** NOTE: this product is not recommended for use in gearboxes with hypoid gears.**

► Advantages

- Excellent protection against wear and load capacity at low speed, high torque and high speed, low torque.
- Thermal stability and excellent resistance to oxidation, which increases the life of the oil.
- Proper lubrication with resistance to channeling at low temperatures.

Characteristic	75W	75W-80	80W	75W-90	80W-90	85W-90	85W-140	Test method ASTM
Kinematic viscosity @ 100 °C, cSt	4.1	8	9.5	15	15.5	17	27	D-445
Viscosity index (VI)	100	130	95	180	105	90	90	D-2270
Flash point, °C	160	170	190	190	200	200	205	D-92
Pour point, °C	-39	-39	-33	-39	-27	-18	-18	D-97
Density @ 15 °C, Kg/m ³	870	875	880	860	900	900	905	D-1298

Typical physical characteristics

* Other grades can be produced upon request.

* Packaging

- 1L. Container Carton (12×1L)
- 2L. Container Carton (6×2L)
- Pail 20L.