

PRODUCT DATA SHEET



Oceanlube Power Series

Marine Trunk Piston Engine Oil specially designed for modern Medium Speed 4-stroke Marine Diesel Engines running on Intermediate Fuel Oil (IFO) or Heavy Fuel Oil (HFO)

Product Description

Oceanlube Power is a trunk piston engine oil designed for use in medium speed diesel engines operating on residual fuels in marine, power generation and industrial applications. The superior additive technology used in this oil provides excellent engine cleanliness & wear protection under different operating conditions. This oil is available in SAE 30 & 40 viscosity grades with a BN (Base Number) ranging from 30 to 90. These oils exhibit a high degree of water tolerance and have better water separation and base retention properties. These oils meet the performance requirements of API CF.

Features & Benefits

- Excellent detergency and dispersancy reduces build-up of soot & black sludge and keeps the engine cleaner.
- Acidic by-products are effectively neutralised and the engine is protected from corrosive wear.
- Better demulsibility characteristics ensure water separation leading to trouble free operation.
- Robust anti-wear technology provides protection against piston & linear wear and good gear performance leading to reduction in maintenance costs.
- Improved thermo-oxidative stability retards oil degradation facilitating extended oil life.

Applications

- Recommended for medium speed diesel engines in marine, power generation and industrial applications operating on residual fuels.
- **Oceanlube Power 3000 & 4000** with a BN of 90 are specifically formulated for engines operating on high sulphur residual fuels. These oils are also specially recommended for those engines where the frequency of topping-up/replenishment is less frequent.
- **Oceanlube Power 3040 & 4040** with a BN of 40 are suitable for engines operating on residual fuels having sulphur content up to 4.0%.
- **Oceanlube Power 3030 & 4030** with a BN of 30 are suitable for engines operating on residual fuels having sulphur content up to 3.0%.
- Also recommended for general lubrication of shipboard equipment where specialised lubricants are not required or use of API CF quality oils are adequate.

PRODUCT DATA SHEET



Typical Properties

Oceanlube Power		۳.۳۰	۴.۳۰	۳.۴۰	۴.۴۰	۳.۰۰	۴.۰۰
Typical properties	SAE Grade	۳۰	۴۰	۳۰	۴۰	۳۰	۴۰
	BN	۳۰		۴۰		۰۰	
API CF		X	X	X	X	X	X
Test Parameters	ASTM Method	Typical Values					
Viscosity @ ۱۰۰°C, cSt	D ۴۴۰	۱۱,۱	۱۴,۰	۱۱,۱	۱۴,۰	۱۱,۱	۱۴,۰
Viscosity @ ۴۰°C, cSt	D ۴۴۰	۱.۰	۱.۳	۱.۱	۱.۴	۱.۱	۱.۴
Viscosity Index	D ۲۲۷۰	۱.۳	۱.۰	۱.۰	۱.۱	۱.۸	۱.۰
Flash Point, °C	D ۹۲	>۲۱۰	>۲۱۰	>۲۱۰	>۲۱۰	>۲۱۰	>۲۱۰
Pour Point, °C	D ۹۷	-۱۸	-۱۸	-۱۸	-۱۸	-۱۸	-۱۸
BN, mg KOH/g	D ۲۸۹۶	۳۰	۳۰	۴۰	۴۰	۰۰	۰۰
Density @ ۱۰ °C, kg/l	D ۱۲۹۸	۰,۸۹۹	۰,۹۰۰	۰,۹۰۰	۰,۹۱۰	۰,۹۱۳	۰,۹۱۸

JUL ۲۰۲۱

Manufactured In IRAN under license from Oceanlube Petroleum Brands In The NETHERLAND.