

PRODUCT DATA SHEET



Oceanlube Power Series

Trunk piston engine oil for medium speed diesel engines operating on distillate fuel, Very Low Sulphur Fuel (VLSFO) <0.5% Sulphur Content and Ultra Low Sulphur Fuel (ULSFO) <0.1% Sulphur Content.

Product Description

Oceanlube Power series are trunk piston engine oil designed for use in medium speed diesel engines operating on distillate fuels and Very Low Sulphur Fuels (VLSFO) having sulphur contents <0.5%. The modern additive technology used in this oil provides superior engine cleanliness & protection. This oil is available in SAE 30 & SAE 40 viscosity grades with a TBN (Base Number) of 12 to 20. These oils exhibit a high degree of water tolerance and meet the performance requirements of API CF.

Features & Benefits

- Superior detergency ensures piston and crankcase cleanliness.
- Improved anti-wear property minimises engine wear and reduces maintenance costs.
- Excellent thermo-oxidative stability retards oil degradation and controls its viscosity.
- Reserve BN ensures protection of engine parts against corrosive combustion products.
- Better demulsibility characteristics ensure water separation leading to trouble free operation.
- Special rust & corrosion inhibitors prevent corrosion of engine parts in severe salt water environment.

Applications

- Recommended for medium speed engines used in marine, power generation and industrial applications operating on distillate fuel, Very Low Sulphur Fuel (VLSFO) having sulphur contents <0.5% and Ultra Low Sulphur Fuel (ULSFO) having Sulphur content less than 0.1%. This product is also suitable for older engines where liner-lacquer is not a potential problem.
- Oils of appropriate BN to be chosen based on the sulphur content of fuel used. Follow manufacturers' recommendation for selection of suitable BN level/ viscosity grade.
- Also recommended for general lubrication of shipboard equipment where specialised lubricants are not required or use of API CF quality oils are adequate.

Typical Properties

*Oceanlube Power *		3012	4012	3010	4010	3020	4020
Typical properties	SAE Grade	30	40	30	40	30	40
	TBN	12		10		20	
API CF		X	X	X	X	X	X
Test Parameters	ASTM Method	Typical Values					
Viscosity @ 100°C, cSt	D 440	10.9	14.0	11.1	14.3	11.1	14.0
Viscosity @ 40°C, cSt	D 440	90	140	98	140	98	140
Viscosity Index	D 2270	99	99	99	100	100	98
Flash Point, °C	D 92	>220	>230	>210	>220	>230	>210
Pour Point, °C	D 97	-18	-18	-18	-18	-18	-18
TBN, mg KOH/g	D 2896	12	12	10	10	20	20
Density @ 10°C, kg/l	D 1524	0.889	0.896	0.891	0.897	0.894	0.900

DEC 2020