



Paroil E Mission Green

Mineral lubricant for Stage 3b/Tier 4 engines

Paroil E Mission Green is a high-performance engine oil intended for the lubrication of all diesel engines as used in our compressors, generators and self-priming diesel pumps, both the latest low-emission models (Euro 4, 5, US 2007, ACEA E9) and previous versions. It meets stringent quality control specifications to ensure your equipment will run smoothly and reliably.

This oil is formulated from a highly refined mineral oil and an advanced additive system, showing excellent high-temperature viscosity retention under extended service. Paroil E Mission Green provides a very high level of protection to all parts of the engine. Overall engine cleanliness is improved under the most severe conditions.

- Superb anti-wear and corrosion protection
- Extremely high oxidation stability
- Balanced composition
- Protection against the harmful effects of soot

- Quality lubricant additives
- Recommended for use in low-emission designs
- Contributes to minimal downtime
- Compliance with latest emission regulations (Euro 4, 5, US 2007, Tier 4 ACEA E9).




Performance:

Performance	Method	Unit	Value
Sulphated ash	ASTM D874		1.0 max
Kinematic viscosity at 40°C	ASTM D 445	mm ² /s	117
Kinematic viscosity at 100°C	ASTM D 445	mm ² /s	15.2
Viscosity index	ASTM D 2270		139
Density at 15°C	ISO 3675	kg/dm ³	0.883
Flash point COC	ASTM D 92	°C	225
Pour point	ASTM D 97	°C	-34

Paroil E Mission Green is optimized for the latest low-emission (EURO 4, 5 and US 2007) EPATIER II, III and IV engines running on low-sulphur diesel for lower oil and fuel consumption. API CJ-4 and ACEA E9,E7.

Capacity:



Capacity	Part number
5 l	1.32 US gal 1630 0471 00
20 l	5.28 US gal 1630 0472 00
210 l	55.48 US gal 1630 0473 00

Equipment:

Atlas Copco portable compressors, generators and portable self-priming pumps, light compaction rollers, plates and rammers, hydraulic power packs, floor saws, trowels, screeds, etc.



Ambient temperature range: -15°C to 40°C
5°F to 104°F



Service intervals:
See user manual