



Technical Data Sheet

- Heavy Duty Protection
- High Temperature
- Lithium Complex

Shell Gadus S3 V460 1

Premium multipurpose heavy duty grease

Shell Gadus S3 V460 Greases are premium, high temperature greases for heavy duty industrial applications. This product is based on high viscosity index mineral oil and a lithium complex soap thickener and contains the latest additives to offer excellent high temperature oxidation performance and other additives to enhance its anti-oxidation, anti-wear and anti-corrosion properties.

Shell Gadus S3 V460 Greases are especially suitable for slow moving, heavy-duty bearings operating at high temperature and under severe load.

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

- **High base oil viscosity to meet leading OEM requirements for slow moving large bearings**
Proven in workroll bending operations in steel plants.
- **Excellent mechanical stability even under vibrating conditions**
Consistency retained over long periods, even in conditions of severe vibration.
- **Enhanced extreme-pressure properties**
Excellent load-carrying performance.
- **Excellent water resistance**
Ensures lasting protection even in the presence of large amounts of water.
- **Effective corrosion protection**
Ensures components/bearings do not fail due to corrosion.
- **High dropping point**
Resistant to high temperatures.

Main Applications



Shell Gadus S3 V460 Greases are used for the grease lubrication of heavy-duty, slow moving bearings used in heavy industries :

- Steel (Continuous casters, Workroll bearings etc)
- Cement
- Paper
- Chemical Industry
- Mining

Specifications, Approvals & Recommendations

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Help Desk.

Typical Physical Characteristics

Properties			Method	Shell Gadus S3 V460 1
NLGI Consistency				1
Colour				Light Brown
Soap Type				Lithium complex
Base Oil Type				Mineral
Base Oil Viscosity	@ 40°C	cSt	IP71 / ASTM D445	440
Base Oil Viscosity	@ 100°C	cSt	IP71 / ASTM D445	28
Cone Penetration, Worked	@ 25°C	0.1mm	IP50 / ASTM D217	325
Dropping Point			IP 396	250
Pumpability Long Distance				Excellent

These characteristics are typical of current production. Whilst future production will conform to Shell's specification,

variations in these characteristics may occur.

Health, Safety & Environment

- **Health and Safety**

Shell Gadus S3 V460 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.epc.shell.com>

- **Protect the Environment**

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

- **Re-greasing Intervals**

For bearings operating near their maximum recommended temperatures, re-greasing intervals should be reviewed

- **Operating Temperature**

-20°C to 140°C (peaks 150°C)

- **Advice**

Advice on applications not covered here may be obtained from your local Shell representative